




### BTI. One stop for all your Pneumatic Solutions.





Check Valves
Air Filters

Pest Control (Critter Stopper) Pressure Relief AlloMaxx Disc Aerators Couplers

MaxxLife Valves
Utility Valves
BlackMaxx Composite

BlackMaxx

Handle

HD Handle
EasyAccess Extension
Easy Torque Actuators

SiphonFlow Hopper Tees

SandHog
Easy Open

**Bottom Drop Low Profile SS** 

The full line of BTI Products
Proudly and Completely Made in the USA



MAC Trailer Aftermarket Parts, Inc.
12241 Rockhill Ave. NE. Alliance, OH 44601
Phone: 800-647-9424 Web: aftermarket.mactrailer.com



Composite Fiber Butterfly Valves

Seats: Black MaxxLife - White MaxxLife\*

Sizes: 2" to 8"

Stem Extensions: 3" - 48"

#### **Features and Benefits:**

Composite Fiber for strength and weight reduction High Flow Rate Reduced Torque No Disc Screws Lighter Weight **Upper Stem Seal Lubrication** Double D Stepped Stem Seat Interlocks to Body MaxxLife FDA Compliant Seat Stainless Steel, Ductile, or AlloMaxx Disc



Replaces Ductile or Stainless Steel Food Grade or Abrasive materials Stronger than Ductile Iron With BlackMaxx allows for 50% reduction in weight 30% more flow than ductile iron disc



Seats: Black MaxxLife and White MaxxLife\*

Sizes: 2" to 12"

Stem Extensions: 3" - 48" **Features and Benefits:** 

**High Flow Rate Reduced Torque** No Disc Screws Lighter Weight **Upper Stem Seal Lubrication** Double D Stepped Stem Seat Interlocks to Body **HD Handle/Stainless Steel Plate** MaxxLife FDA Compliant Seat

Stainless Steel, Ductile, or AlloMaxx Disca great food grade alternative to stainless





Same features as MaxxLife but only available in the following configuration:

Seat: Black Buna-N Disc: Ductile Iron



 The standard BlackMAXX Composite HD Handle is 43% lighter than an industry standard stamped steel handle

- The BlackMAXX handle is 25% lighter than an aluminum HD Handle
- Fastener free handle retention • Static Shock resistant interlocking throttle plate
- Corrosion resistant



· Priced at or below imports

Lifetime Warranty

Fits all standard butterfly valves and is available in two sizes for your specific application.



#### **Features and Benefits:**

Keeps user clear of hot supply lines Avoid back strain - lowering workers' comp claims

Multi-Angle to fit any situation **Lubrication Chamber** Booted to keep road dirt and grime out





#### **Features and Benefits:**

Aluminum Body for Light Weight Stainless Steel Trigger for Long Life Corrosion-resistant composite

trigger for smooth operation



# Ultra-Lightweight Aeration Butterfly Valve

### Features and Benefits:

Connect directly to air line Weighs a fraction of conventional aeration valves - 1.5 lbs!

Same flow as conventional ball valves 4 configurations:

King nipple to female King nipple to king nipple Female to female King nipple to flanged

Other connections available upon request

### Provides superior performance and critical weight-savings



#### **Features and Benefits:**

**Quieter Operation** 

No negative effects due to moisture **Small Foot Print** 

**Less Air Consumption** 

Unique design allows fail safe operation 2 Year Full Warranty

One Internal Moving Part and no Corrosion Prone Spring





**Bottom Drop or Straight** 

**Features and Benefits:** 

**EXTREME** Wear Resistance

Unique Ledge Protects Critical Wear Areas BTI's Duralron that Provides Over Twice the Wear Patented SiphonFlow Technology for Faster Unloading

Thicker Construction in Critical Wear Areas

**BlackMaxx** 

US Patent #10.145.500

**3 Connection Configurations** 

Straight

• Female Cam connection

Male Cam connection

BTI SandHog™ Elbow **BlackMaxx** Configurations: two cam and groove configurations: female to male and male to female Angle: 45° or use 2 to make 90° **Features and Benefits: EXTREME** Wear Resistance for highly abrasive materials like frac sand Unique Spherical Pocket Design **Protects Critical Wear Areas** Side Unloading as well as Rear Unloading Original Duralron®

## BTI SiphonFlow™ EasyOpen **Hopper Tee**

Original Duralron®



#### **Features and Benefits:**

No Bolts - Easy to Remove for Cleaning Easy to Adjust Faster Unloading Easy to Clean Polymer and Oil Impregnated **Bushings at Pivot Points** Eliminates the Danger of Contamination Fewer Parts Means Less Maintenance

# BTI'S ULTRA-LIGHT MANHOLE ASSEMBLY

Self-Aligning Lid Gasket - Keeps lid aligned and metal shavings from entering your load.

Wearplate - New design allows for easy and quick replacement of wear plates.

**BTI's Never-Seize Dry Bulk** Manhole Adjusters are quaranteed to keep your working better. Never-seize

adjusters operating longer and adjusters come with a 10-year warranty. Parts are interchangeable with leading manufacturers.



### **BTI SiphonFlow™ Straight Hopper Tee**



Sizes: 5" - 6" - 8"


Material: Aluminum or Abrasion Resistant Duralron™

#### **Features and Benefits:**

Fastest Unloading Tee on the Market Lightweight • Longer Lasting

Creates Less Turbulence - Reduces Heat and Friction

Approx. 300 SCFM's More Flow Than Any Tee on the Market Today





### **BTI SiphonFlow**™ **Bottom Drop Hopper Tee**



Sizes: 5" - 6" - 8"

Material: Aluminum or Abrasion Resistant Duralron™

#### **Features and Benefits:**

No Bolts . Always Perfectly Aligned to Prevent Accidental Discharge Faster Unloading • Easy to Clean Polymer Bushings at Pivot Points

## **BTI Critter Stopper**



Sizes: 3" - 4" **Eliminates Small Rodents and Insect Contamination** Flap Allows Air Out But Nothing In Attaches to End of Blow-Down Line

Port Configurations: 1-3 **Housing:** Clear or Natural **Features and Benefits:** Up to 20% Faster Unloading **Increased Pressure Velocity** 

**Prevents Back Flush** 



Rubbers: Blue or FDA Approved White Rubber designed to Last Longer with out premature cracking or splitting.

# All-in-One Coupler



**Body:** Aluminum or BlackMaxx Composite Fiber Sizes: Aluminum: 3" - 4" - 5" BlackMaxx: 4" Closure: Bolt-On Tee or Cam Handle Gasket: White FDA Approved - Solid or Split **Features and Benefits:** 

One Coupler for Plain to Plain, Groove to Plain, and Groove to Groove Light Weight Aluminum Die Cast

Eliminates Unnecessary Parts Costs Hinge Design Matches Gasket Curve - Eliminates

Pinching Split Gasket Seals First time and Every Time **Provides Continuous Grounding** FDA Approved Lubricant in Gasket Eliminates

**Need for Additional Lubrication** 

**Cuts Cleaning Time** Polymer Bushings Eliminates Galling and Seizing Lock Pin Provides Secure Closure

# **Groove to Groove Couplers**

### **Bolt-On and Cam Handle**

**Body:** Aluminum Sizes: 3" - 4" Closure: Bolt-On Gasket: White FDA Approved -Solid or Split Features and Benefits: Grooved to Grooved, Grooved to Plain, and Plain to Plain Light Weight Aluminum Die Cast Provides Continuous Grounding Split Gasket Seals First time and Every Time FDA Approved Lubricant in Gasket





Sizes: 2", 3" and 4" Flat Poppet Gasket: White FDA Approved **Features and Benefits:** Long Life Coil Spring . Light Weight

Spring Housing Protects Load from Contamination Fewer Internal Parts- Reduced Risk of Contamination Bell Housing Provides More Open Area & Less Back Pressure **Guide Bushings Regulate Opening and Protects Spring** Flat face poppet allows for more open area for flow and less back pressure. Self-sealing gasket design.





Sizes: 2" Release: Adjustable - Fixed -Manual Pressure Ratings: 5-30 PSI Features and Benefits: Long Life Coil Spring Fewer Internal Parts-Light Weight and Reduced Risk of Contamination

Bell Housing Provides More Open Area and Less Back Pressure High to Low Temperatures lale Cam Lock Fitting, Male Anodized Threads and **Female Anodized Threads** FDA Approved Seat Tamper Proof Body



#### Sizes: 2" Features and Benefits:

Machined top and bottom stainless steel spring guide tubes to ensure consistent function and repeatability

Unique poppet and spring design allows for smooth and consistent air flow, eliminating "air shutter" found with standard poppet designs which causes fluctuating air pressure

Precision machined S.S. poppet with optimized huddle chamber One-piece FDA-Compliant High-Temperature Diaphragm to protect and eliminate contamination to the working components from dirt, water and ice

**3 Connection Options** 

Male 2" Cam Fitting • Male 2" NPT Threads • Female 2" NPT Threads Hard anodized to protect and extend life Multiple Configurations Available

Non-Adjustable, Manual-Release and Adjustable Tamper-Proof Seal

### **BTI Pneumatic Conveying** Filter Screen

Sizes: 4" - 5" - 6" Screen Options: 1/4", 3/8" and 7/16" sizes Connections: Male Pipe Threads, Male Cam Lock, Female Cam Lock Features and Benefits: Bell Housing Creates 40% More Open Area

- Flow is Not Restricted One-Piece Cast Aluminum Housings . Lighter than Convention-

al Filters • Filter Screen is Molded in to Gasket • Quick Coupler makes Cleaning Fast and Easy • Tamper Proof - If Filter is Removed, Unit Will Not Hold Pressure

### **SpinFlow** Filter/Silencer

**Features and Benefits:** Silencer Built in to Unit **Reduces Back Pressure** Reduces Heat Build Up Airflow Spin Helps to Utilize Complete Filter Surface Single Lever Cam Lid Easy to Clean

**Fewer Adjustments** 

Tamper Proof



**Features and Benefits:** Tapered end caps for easy installation Permanent date stamp Top mounted temperature indicator
Spiral welded core that is welded to
the end caps for extra strength Center band more stability and strength in a side air inlet housing High strength potting material Optional FDA Compliant Teflon®

membrane

### **BTI Low Profile Stainless Steel Hopper Tee**

Sizes: 5" & 6" Material: Light Weight Stainless Steel

**Features and Benefits:** 

Introducing the industry's first American made, food grade, investment cast, ultra-light weight, low profile hopper tee.





### **BTI Trailer Mounted** Air-to-Air Cooler

The ultimate protection for heat sensitive loads

Two Configurations: Discharge/Intake on Fan Side and Discharge/Intake opposite Fan Side

**Features and Benefits:** 

Provides cooled air to the dry bulk material.

Cooler is automatic - no special procedure is required.

Virtually maintenance free.

Requirés no external water, air, or electric source. Victaulic groove on the piping stub coming from the cooler, intake and discharge ports.

Compact, light, inexpensive, and does not affect the size of the trailer.

### **Light Weight Front Mount**

**SpinFlow Filter System** 

Over 5 lbs. lighter Front Hose Inlet Connection Exterior Filter Guide Protects from Load contamination



### **Light Weight Standard** SpinFlow Filter System

Over 5 lbs. lighter

4-inch Rear Connector Exterior Filter Guide Protects from Load contamination

